

# Abutment Flashings

## GreenCoat® Pural BT



Abutment Flashings are made with a GreenCoat® Pural BT coat and are produced on-site at the Cladco warehouse from multi-layered galvanised steel. Each Flashing is pre-coated with a tough GreenCoat® Pural BT coating to match Cladco GreenCoat® Pural BT Sheets.

Abutment Flashings have a 110-degree angle and can flex between 10 to 15 degrees both ways during installation.

### Cladco Abutment Flashings

This coating has a weather-resistant GreenCoat® Pural BT finish that gives high scratch resistance and durability, with excellent longevity for any roofing project such as a lean-to building.

Secure to steel sheets below using 22mm Stitcher Screws and ensure a 200mm overlap between each Abutment Flashing.

Please note: These 200mm x 200mm Flashings provide a coverage of 190mm x 190mm due to the 10mm safety welt.

SPECIFICATIONS	
Length	3 metres
Sizes available	200mm x 200mm (190mm x 190mm coverage)

**PLEASE NOTE** – Extra care should always be taken when handling metal sheets and flashings we advise using the correct type of Glove when handling or moving metal sheets and flashings.



01837 659901 [info@cladco.co.uk](mailto:info@cladco.co.uk)  
[www.cladco.co.uk](http://www.cladco.co.uk)

Beardown Road, Exeter Road Industrial Estate, Okehampton EX20 1UA