

FRAME PROTECTION DECK TAPE, 20M

Cladco Frame Protection Deck Tape is made from non-butyl, self-sealing adhesive and is designed to go on timber joists, around exposed ends and between fixings and fasteners to prevent water intrusion into the wood.

Frame Protection Deck Tape will effectively reduce the risk of rot and moisture damage setting in, which could compromise the structural integrity of a timber base. As rainwater run-off is less absorbed into Composite Decking Boards, timber substructures can tend to become more saturated with water, which can lead to weaknesses in the frame over time. A layer of Deck Tape applied to timber joists will form a lasting, non-deteriorating protective surface.

Deck Tape is easy to tear and can be repositioned, if required. The Tape is temperature stable down to -40C and up to +93C, which means Frame Protection Deck Tape can be attached to freezing or damp timber. Measuring a width of 65mm, apply Deck Tape to the top side of each supporting wooden joist, allowing for slight overlap on the sides of the joists, before installing your Decking Boards.

As a guide, a roll of Deck Tape (20m) is required for each 6m² area of Decking.



SPECIFICATIONS	
Roll Length	20 metres
Tape Width	65mm
Tape Colour	Black



Benefits of Deck Tape

- Prevents rot and weathering within timber deck frames
- Creates a water-proof seal between joists and decking
- Reduces moisture pooling on timber joists
- Increases lifespan of wooden joists or posts
- Manufactured from strong polymer acrylic adhesive
- UV stable for long life

PLEASE NOTE – Images are used for illustration purposes only, actual item may vary slightly from the image supplied.



01837 659901 info@cladco.co.uk
www.cladcodecking.co.uk

Beardown Road, Exeter Road Industrial Estate, Okehampton EX20 1UA

