

3.6M WOODGRAIN EFFECT BULLNOSE BOARD NORDECK RANGE

Cladco Nordeck woodgrain effect bullnose boards perfectly complement Nordeck decking boards by providing a neat, curved edge for a polished finish. Manufactured from durable PVC-ASA materials, these boards resist fading, staining, and scratching. Featuring a luxurious textured surface with a natural wood effect, Nordeck bullnose boards are available in six contemporary colours. Backed by a 20-year structural warranty, they offer long-lasting style and performance for your decking project.

*When installed with Cladco Recycled Plastic Joists.

COLOUR RANGE



BOARD SPECIFICATIONS

Length	3.6m
Width	150mm
Thickness	32mm
Weight	11.16kg

TEST CERTIFICATIONS

Slip Resistance	DRY - Low-slip potential WET - Low-slip potential
SKU	(Chestnut) PVCBCN36 (Silver Birch) PVCBSB36 (Cedar Wood) PVCBCW36 (Walnut) PVCBWN36 (Ash Grey) PVCBAG36 (Ebony) PVCBEB36 (Black) PVCBBL36



Please Note: Images are for illustration purposes only. Actual products may vary slightly from those shown.



MATERIALS

Made from a robust PVC core encased in a tough ASA resin shell, these boards offer exceptional durability and long-lasting performance.



SURFACES

Featuring a premium embossed woodgrain effect surface, these boards authentically replicate the natural look and texture of timber.



ACCESSORIES

Nordeck bullnose boards can be installed using either hidden deck fasteners for a clean, discreet fix, or Cladco high strength adhesive for a strong, seamless bond.



RESISTANCE

Unlike timber, Nordeck decking is resistant to stains, scratches, UV rays, and moisture damage,



WARRANTY

Cladco Nordeck bullnose boards come with a 20-year structural warranty for your peace of mind.

PVC-ASA MATERIAL

Cladco Nordeck woodgrain effect decking features a dense PVC core encased in a durable ASA resin shell, delivering exceptional resilience against weather, scratches, UV fading, and rot. This tough PVC-ASA capstock material is ideal for use in damp environments or near the ground, such as around pools or hot tubs, thanks to its moisture-resistant properties.

With a beautifully embossed surface, Nordeck decking replicates the natural look and feel of timber while offering superior resistance to everyday wear, stains, and scratches. Its outstanding UV resistance ensures it retains its original colour even after prolonged sun exposure.

AFTERCARE

Nordeck woodgrain effect decking is low maintenance and easy to clean using warm, soapy water when necessary. Occasional use of a pressure washer is possible but should be kept at least 250mm to 300mm away from the decking surface to prevent damage. Proper care will keep your Nordeck decking looking exceptional for years to come.

INSTALLATION ADVICE

Lay your Decking

Once the main decking structure is complete, you can install Cladco Nordeck bullnose boards to achieve a seamless, polished finish. These bullnose boards are fixed securely around the framework, providing a neat curved edge that enhances the overall look of your decking project.



Install using SPEEDDEKZ Deck Screws

Cladco Nordeck bullnose boards can be installed using SPEEDDEKZ deck screws for a secure fixing. Please note, this method will leave the screw heads visible on the surface of the boards, providing a strong and reliable attachment.


Install using Hidden Deck Fasteners

For a clean, hidden finish, install Cladco Nordeck woodgrain effect bullnose boards using our hidden deck fasteners. This system includes 65mm screws and colour-matched plugs that conceal the screw heads, creating a seamless and professional appearance.



For detailed information about installation, please read our Nordeck woodgrain effect decking installation guide.

PRODUCT ACCESSORIES



DECKING BOARDS



FASCIA BOARDS



CLADCO HIGH STRENGTH ADHESIVE



COMPOSITE JOISTS



TIMBER JOISTS



WEED MAT & PINS BUNDLE



SPEEDDEKZ 316 STAINLESS STEEL SCREWS



MAGNETIC PHILLIPS IMPACT SCREWDRIVER BITS



65MM HIDDEN DECK FASTENERS